
Partnership. With Guarantee.

Manifold K-BUI
for service units series FRL



Design type	Manifold with one outlet
Connection Air outlet	G1/4" according to ISO228/1
Materials	Housing Acetal resin (POM), Threaded connection Brass
Function	Manifold module for FRL series air service units
Mounting position	any
Medium	filtered and lubricated or non-lubricated compressed air
Medium temperature	+5...+50°C
Ambient temperature	+5...+50°C
Inlet pressure	max. 16bar for size 1/4", max. 12,5bar for Size 3/8" up to 3/4"
Scope of delivery	including fastening element


Series FRL - 1/4"




usable as	Typ
Intermediate module	K-BUI-H
Input module	K-BUI-H-I
Output module	K-BUI-H-0

+43 512 52076
austria@stasto.eu
© STASTO Automation KG


Series FRL - 3/8"

	usable as	Typ
	Intermediate module	K-BUI-E
	Input module	K-BUI-E-I
	Output module	K-BUI-E-0

Series FRL - 1/2"

	usable as	Typ
	Intermediate module	K-BUI-F
	Input module	K-BUI-F-I
	Output module	K-BUI-F-0

Series FRL - 3/4"

	usable as	Typ
	universal	K-BUI-G

Illustrations non-binding
Design, dimensional and material changes reserved