


Way valves with foot actuation
Series PM122, PM137, PM138





PM122


PM138





PM137

Design type	PM122/PM138 Slide valve, PM137 Poppet valve, with foot actuation
Connection	G1/4" according to ISO228/1 or rather 4mm Push-in fitting
Nominal size	PM122/PM138 DN8mm, PM137 DN2,5mm
Medium	filtered and lubricated or non-lubricated compressed air
Medium temperature	0...+40°C
Flow rate	PM122/PM138 1080Nl/min, PM137 90Nl/min
Ambient temperature	-10...+50°C
Operating pressure	PM122/PM138 3...10bar, PM137 0...10bar
Note	CAD files are available in the STASTO Store at www.stasto.eu



PM122 5/2-way valve G1/4"

		Actuation	Type
		Foot/spring	PM122-14
		Foot/latching	PM122-14-BS

PM138 5/2-way valve G1/4"

		Actuation	Type
		Foot/spring	PM138-14
		Foot/latching	PM138-14-BS

PM137 3/2-way valve 4mm Push-in fitting

		Actuation	Type
		Foot/spring	PM137-04

Illustrations non-binding
Design, dimensional and material changes reserved

+43 512 52076
austria@stasto.eu
© STASTO Automation KG

+43 512 52076
austria@stasto.eu
© STASTO Automation KG