



Spojnice Serija CI.S-B-A




Konstrukcija	Utičnice spojnice i utikači spojnice, obostrano zaporno, ISO 7241-1 Serija B
Materijali	Telo, ventil i konektor Mesing, Opruga od nerđajućeg čelika 1.4310, Zaptivka FKM
Medij	Gasovi i tečnosti, koje ne napadaju korišćene materijale
Temperatura medijuma	-20...+125°C
Radni pritisak	vidi tabelu
Protok	vidi Dijagram protoka

CICS-F Utičnica spojnice - Unutrašnji navoj


	A	DN [mm]	Veličina	D	L	L1	SW	maks. radni pritisak [bar]	Protok [l/min]	Težina [g]	Tip
	G1/8"	3,2	02	23	50	9	18	220	6	85	CICS1/8-F18-B-A
	G1/4"	6,3	04	28	56	13	19	200	16	108	CICS1/4-F14-B-A
	G3/8"	10	06	35	64	13	24	150	25	197	CICS3/8-F38-B-A
	G1/2"	12,5	08	44	71,6	15	30	170	60	536	CICS1/2-F12-B-A
	G3/4"	20	12	52	89	17	36	100	110	712	CICS3/4-F34-B-A
	G1"	25	16	62	106	19	41	140	150	911	CICS1-F10-B-A

CIPS-F Utičnica spojnice - Unutrašnji navoj

	A	DN [mm]	Veličina	L	L1	SW	maks. radni pritisak [bar]	Protok [l/min]	Težina [g]	Tip
	G1/8"	3,2	02		9	18	220	6	20	CIPS1/8-F18-B-A
	G1/4"	6,3	04		13	19	200	16	36	CIPS1/4-F14-B-A
	G3/8"	10	06		13	22	150	25	61	CIPS3/8-F38-B-A
	G1/2"	12,5	08		15	27	170	60	109	CIPS1/2-F12-B-A
	G3/4"	20	12		17	34	100	110	215	CIPS3/4-F34-B-A
	G1"	25	16		19	41	140	150	339	CIPS1-F10-B-A



Dijagram pada pritiska:



Ilustracije neobavezujuće

Zadržavamo pravo na konstruktivne, dimenzione i materijalne izmene.

Pneumatika / Priključci i spojnice za pneumatiku / Spojnice / čep spojnice standard / spojnica prema ISO 7241-1 serije B - mesing dvosmerno zaptivanje

