
Straight union nut, taper-sealing - Brass



Connection	1/2"...2" according to ISO7/1
Material	Plain brass
Medium	Compressed air, neutral gases, Liquids that do not chemically attack the materials
Medium temperature	-200...+200°C
Operating pressure	0...16bar

TH59 Straight union nut - taper-sealing



D1	D2	L1	CH1	CH2	Weight [g]	Type
R 1/2"	RP 1/2"	53	30	25	102	TH59C-12-B-Z
R 3/4"	RP 3/4"	63	37	30	153	TH59C-34-B-Z
R 1"	RP 1"	67	46	39	272	TH59C-10-B-Z
R 1 1/4"	RP 1 1/4"	75	52	46	414	TH59C-114-B-Z
R 1 1/2"	RP 1 1/2"	81	59	54	764	TH59C-112-B-Z
R 2"	RP 2"	91,5	75	66	850	TH59C-20-B-Z

Illustrations non-binding
Design, dimensional and material changes reserved

Pneumatics / Fittings and couplings / Other materiales - P05 / Detachable hex nipple Conical sealing Female thread/Male thread Series TH59C-B / [TH59C-12-B-Z] Detachable hex nipple Conical sealing Female thread/Male thread TH59C-12-B-Z

+43 512 52076
austria@stasto.eu
© STASTO Automation KG